

G4 Industry First P25 Voice Pager



Available in 700-800 Mhz
Supports Multiple P25 Systems
Text Messaging Capability
IP67 RATING Waterproof & Dustproof
High Impact Resistant Color Screen
Custom Wav File Alerts

P25 Trunking
P25 Conventional
Conventional
Out of Range Alert
Location of Incident GPS
32 Minutes Voice Storage
32 Minutes Voice Memo
Image Transfer
Bluetooth
Ruggedized Housing
2 Year Standard Warranty/ 3 Year Addition Available

Unication USA is proud to introduce our newest innovation, the ground-breaking G4 P25 Voice Pager. This cutting edge device is the first voice pager capable of supporting multiple P25 systems.

The G4 is built to be as tough as the heroes it serves. Featuring an IP67 rating, the G4 is waterproof, dustproof and fully submersible at up to 3 feet/30 minutes. The rugged housing and high impact resistant color screen is designed to endure the punishing environments of first responders. The G4 is a software-defined pager that allows you to access software updates to add the latest features and capabilities to your device.

www.UnicationUSA.com
[www.Facebook.com/UnicationUSAInc](https://www.facebook.com/UnicationUSAInc)



Unication


G4 Features

Digital Support Protocol:
 P25 Conventional, P25 Trunking, Conventional
 Selective Call & Monitor
 Lithium Ion Battery
 32 Minutes Voice Storage
 32 Minutes Voice Memo
 High Impact Resistant Color Screen
 64 Channels
 Rejects Cellphone Interference
 Message Lock
 Duty and Auto On/Off feature
 Bluetooth (compatible with most phones and headsets)
 Memory Storage: Text, Voice, Timestamp

Additional Information

Best in Class Message Reception
 Submersible (3 ft./30 minutes)
 Software-defined Technology
 Carry Style: Belt Clip
 Temperature Range:
 -30 C ~ +60 C
 Special Rubberized Housing
 Weight without battery: <220g
 Size (mm): 102 x 61 x 31.5
 8 Position Selector Knob
 Characters and Length:
 9 Lines x 22 Characters
 Display Length: 30.6x40.8/mm

Technical Specifications

RF Perf/Band	700/800 MHz	
Sensitivity	>-116dBm	
Sensitivity/12dB SINAD (uV/M)	>6 uV/M	
Frequency Stability (ppm)	+/-1	
Adjacent Channel Selectivity	>60dB	
Spurious	>70dB	
Image Rejection	>70dB	
Audio Output Linear	>300mw	
Audio Distortion	<3%	
Speech Output (From 12 inches)	94dB +/- 2 dB SPL	
Alert Output (From 12 inches)	96 +/- dB SPL	
Dust/Water Proof Level	IP67	
UL	Class I, Div. II	
FCC	FCC Part 15	
MIL-STD	810E, Procedures 1 for Driving Rain	
Channel Spacing	10/12.5/20/25 kHz	
Frequency Band	700/800 MHz: 764 MHz-870 MHz	